

WEIGHTS AND DIMENSIONS (SUPPLEMENTAL DATA)

		Operating Weight	Tipping Load			Overall Width (Outside Tire)	Tread	Vertical Dimensions	Overall Length
			Straight	Full Turn					
Remove ROPS Canopy and Cab (for transport only)	lb (kg)	-2580 (-1170)	-2250 (-1020)	-1940 (-880)	in (mm)			-1'4 ¹ / ₈ " (-410)	
Remove Optional Counter Weight	lb (kg)	-1260 (-570)	-3110 (-1410)	-2650 (-1200)	in (mm)				
Tires: 35/36-33-24PR (L-5)	lb (kg)	+1500 (+680)	+1040 (+470)	+900 (+410)	in (mm)	-4 ³ / ₄ " (-120)		+1" (+25)	-1 ³ / ₈ " (-35)
35/65-33-24 (L-4) (75% CaCl ₂)	lb (kg)	+5950 (+2700)	+8510 (+3860)	+7280 (+3300)	in (mm)				
35/65-33-24 (L-5) (75% CaCl ₂)	lb (kg)	+7450 (+3380)	+9550 (+4330)	+8180 (+3710)	in (mm)			+1" (+25)	-1 ³ / ₈ " (-35)
Air conditioner (Deletion)	lb (kg)	-200 (-100)	-180 (-80)	-150 (-70)	in (mm)				
Belly Guard (Rear Frame)	lb (kg)	+310 (+140)	+440 (+200)	+375 (+170)	in (mm)				

Tread 8'8⁹/₁₆" (2050mm)
 Width (outside tire) 11'8⁹/₁₆" (3570mm)
 Width (outside bucket) 12'4⁷/₁₆" (3770mm)

Equipped with Rock-V-Edge bucket with teeth,
 35/65-33-24PR (L-4) Tire and Open ROPS
 and Enclosed Cab

