

WEIGHTS AND DIMENSIONS (SUPPLEMENTAL DATA)

	Operating Weight	Tipping Load		Overall Width (Outside Tire)	Tread	Vertical Dimensions	Overall Length		
		Straight	Full Turn						
ROPS Canopy (Instead of ROPS Cab)	lb (kg)	-310 (-140)	-330 (-150)	-290 (-130)	in (mm)				
Remove ROPS Cab (for transport only)	lb (kg)	-1100 (-500)			in (mm)		-10' 15/16" (-275)		
Remove Optional Counterweight	lb (kg)	-770 (-350)	-1760 (-800)	-1540 (-700)	in (mm)				
Tires: 20.5-25-12PR (L-3)	lb (kg)	+300 (+135)	+220 (+100)	+190 (+85)	in (mm)				
23.5-25-12PR (L-2)	lb (kg)	+1610 (+730)	+1200 (+545)	+1030 (+465)	in (mm)	+2 (+50)	+1 5/8" (+40)	+2 3/8" (+60)	-2 1/8" (-55)
23.5-25-12PR (L-3)	lb (kg)	+2030 (+920)	+1520 (+690)	+1300 (+590)	in (mm)	+2 (+50)	+1 5/8" (+40)	+2 3/8" (+60)	-2 1/8" (-55)
23.5-25-12PR (L-3) with 75% CaCl ₂	lb (kg)	+1800 (+815)	+2690 (+1220)	+2290 (+1040)	in (mm)				
Air conditioner (Deletion)	lb (kg)	-220 (-100)	-240 (-110)	-210 (-95)	in (mm)				
Belly Guard (rear frame)	lb (kg)	+130 (+60)	+120 (+55)	+100 (+45)	in (mm)				

Base Tire 20.5-25-12PR (L-2)

Tread 6'8 3/4" (2050mm)
 Width (outside tire) 8'5 3/4" (2585mm)
 Width (outside bucket) 8'9 1/8" (2670mm)
 Equipped with GSC bucket with bolt on cutting edge
 20.5-25-12PR (L-2) Tire and ROPS Cab

