

WEIGHTS AND DIMENSIONS (SUPPLEMENTAL DATA)

	Operating Weight	Tipping Load		Overall Width (Outside Tire)	Tread	Vertical Dimensions	Overall Length	
		Straight	Full Turn					
Remove ROPS Cab (for transport only)	lb (kg)	-1100 (-500)	-950 (-430)	-820 (-370)	in (mm)			
Remove Optional Counterweight	lb (kg)	-770 (-350)	-1895 (-860)	-1610 (-730)	in (mm)			
Tires: 23.5-25-16PR (L-2)	lb (kg)	-1785 (-810)	-1280 (-580)	-1100 (-500)	in (mm)	-3 ³ / ₈ " (-85)	-2 ³ / ₈ " (-60)	+2" (+50)
23.5-25-16PR (L-4)	lb (kg)	-465 (-210)	-330 (-150)	-285 (-130)	in (mm)	-3 ³ / ₈ " (-85)	-2 ³ / ₈ " (-60)	+2" (+50)
23.5-25-16PR (L-5)	lb (kg)	+595 (+270)	+440 (+200)	+375 (+170)	in (mm)	-3 ³ / ₈ " (-85)	-2 ³ / ₈ " (-60)	+2" (+50)
23.5-25-16PR (L-3)	lb (kg)	-1435 (-650)	-1035 (-470)	-880 (-400)	in (mm)	-3 ³ / ₈ " (-85)	-2 ³ / ₈ " (-60)	+2" (+50)
26.5-25-20PR (L-4)	lb (kg)	+615 (+280)	+440 (+200)	+375 (+170)	in (mm)			
26.5-25-20PR (L-5)	lb (kg)	+2225 (+1010)	+1610 (+730)	+1365 (+620)	in (mm)			
23.5-25-16PR (L-3) with 75% CaCl ₂ for logging	lb (kg)	+950 (+430)	+2515 (+1140)	+2160 (+980)	in (mm)			
26.5-25-20PR (L-3) with 75% CaCl ₂ for logging	lb (kg)	+3220 (+1460)	+4805 (+2180)	+4125 (+1870)	in (mm)			
Air conditioner — Deletion	lb (kg)	-220 (-100)	-175 (-80)	-155 (-70)	in (mm)			
Belly Guard (rear frame)	lb (kg)	+220 (+100)	+420 (+190)	+355 (+160)	in (mm)			

Base Tire 26.5-25-20PR (L-3)

Tread 7'3³/₄" (2230mm)
 Width (outside tire) 9'7³/₈" (2930mm)
 Width (outside bucket) 10'2¹/₁₆" (3100mm)

Equipped with GSC bucket with bolt on cutting edge
 26.5-25-20PR (L-3) Tire and ROPS Cab

